

Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Dyna-Plex 21C HD 1000

Medium duty cutting and grinding oil

Product Code: 14773

Miller Industrial Fluids, A PetroChoice Company

1751 W. Raymond Street Indianapolis, Indiana 46221 Website: www.petrochoice.com

1-317-634-7300 Telephone

1-800-424-9300 US, Canada, Puerto Rico, Virgin Island - Emergency telephone (CHEMTREC)

+1-703-527-3887 International / Maritime Emergency telephone (CHEMTREC)

2. HAZARDS IDENTIFICATION

OSHA/HCS Status:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the

substance or mixture: Aspiration Hazard – Category 1

GHS Label Elements Hazard Pictogram:



Signal Word: DANGER

Hazard Statement: H304 – May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention: Do not breathe gas, mist, vapors or spray.

Response: IF SWALLOWED: Immediately call a POISON CENTER or physician. Do

NOT induce vomiting.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other Hazards: None known

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name: None Formula: Mixture

Other means of identification: None CAS Number/other identifiers: None

Component	CAS Number	Concentration %
Petroleum distillates, solvent dewaxed light paraffinic	64742-56-9	80-90
Alkanes, C21-C28, chloro	63449-39-8	1-5

4. FIRST AID MEASURES

Eyes

Rinse immediately with water. Remove contact lenses, if safe and possible to do. Continue rinsing with water for at least 15 minutes. Keep impacted eye(s) wide open while rinsing. If eye irritation persists, consult a specialist.

Inhalation

Move person to an area with fresh air if breathing is difficult. Keep person at rest in a position comfortable for breathing. If symptoms persist, call a physician.

Skin Contact

Take off contaminated clothing and shoes immediately. Wash off affected area with plenty of soap and water. If symptoms persist, call a physician.

Ingestion

Rinse mouth with plenty of water and drink plenty of water afterwards. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Most Important Symptoms/Effects, Acute and Delayed:

Skin irritation, eye redness and tear formation.

Indication of any immediate medical attention and special treatment needed:

If necessary, treat symptomatically

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Use dry chemical, foam, carbon dioxide (CO₂) or water spray or water fog.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards from combustion

Hazardous combustion products may include oxides of carbon and sulfur. May produce irritating fumes and smoke.

Special protective equipment for fire-fighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, emergency procedures

Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. If significant spillages cannot be contained, local authorities should be advised.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where possible. Absorb in vermiculite, dry sand or other non-combustible absorbent material then place into containers. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental precautions

Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Avoid discharge into drains, watercourses or onto the ground. If the product contaminates rivers and lakes or drains, then inform the respective authorities.

7. HANDLING AND STORAGE

Precautions for safe handling

Do not breathe dust, fume, gas, mist, vapors or spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. All handling should take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

Conditions for safe storage

Keep away from heat, sparks and open flame. Store in a well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

OSHA

Component	Туре	Value
Petroleum distillates, solvent-dewaxed light paraffinic	PEL	5 mg/m ³

ACGIH

Component	Туре	Value
Petroleum distillates, solvent-dewaxed light paraffinic	PEL	5 mg/m ³

NIOSH

Component	Туре	Value
Petroleum distillates, solvent-dewaxed light paraffinic	TWA	5 mg/m ³
	STEL	10 mg/m ³

Appropriate Engineering Controls:

Adequate ventilation should be provided whenever the material is heated or mists are generated. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual Protection Measures, such as Personal Protective Equipment:

Eye/Face protection

Goggles/face shield are recommended.

Hand protection

Polyvinyl alcohol or nitrile rubber gloves are recommended.

Skin and body protection

Chemical/oil resistant long-sleeve clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection

If vapors/mist concentration exceed the exposure limit(s), and appropriate certified respirator must be used.

General Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber **Physical state:** Liquid

Odor: Mild

Odor Threshold: Not available

pH: Not available

Melting point/freezing point: Not available

Initial boiling point and boiling range: >560°F (>293.3°C)

Flash point (Cleveland Open Cup): >330°F (>165.6°C) COC, ASTM D92

Evaporation Rate: Not available

Flammability (solid, gas): Not available

Lower/upper flammability or explosive limits:

Flammability limit Lower %: Not available Upper %: Not available

Explosive Limit

Lower %: Not available Upper %: Not available

Vapor pressure: Not available Vapor density: Not available

Relative density: 0.87 @ 60°F (15.56°C)

Solubility in water: Insoluble

Partition Coefficient (n-octanol/water): Not established Auto-ignition Temperature: >600 (315.6°C) ASTM E659

Decomposition Temperature: Not available **Viscosity:** 15 cSt @ 104°F (40°C) ASTM D445

10. STABILITY AND REACTIVITY

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability: Stable

Possibility of hazardous reactions: Product will not undergo hazardous polymerization

Conditions to avoid: Heat, flames and sparks. Avoid elevated temperatures and excessive heat.

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Decomposition products include carbon monoxide, carbon

dioxide and/or low molecular weight hydrocarbons. Combustion gases may contain oxides of carbon and

sulfur.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Ingestion: May cause gastrointestinal irritation and discomfort if swallowed. Do not induce vomiting.

Vomiting may increase risk of product aspiration.

Inhalation: May be fatal if swallowed and enters airways.

Skin Contact: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

Eye Contact: May be irritating to eyes.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Not available

Information on Toxicological Effects

Acute Toxicity: Not classified.

Skin Corrosion/Irritation: May be irritating to skin.

Serious Eye Damage/Eye Irritation: May be irritating to eyes.

Respiratory or Skin Sensitization

Respiratory Sensitization: Not a respiratory sensitizer.

Skin Sensitization: Not a skin sensitizer.

Mutagenicity: Non-mutagenic

Carcinogenicity: This product contains a very long chain chlorinated paraffin. Based upon data

from short chain chlorinated paraffins, the risk of cancer cannot be excluded with

prolonged exposure.

Reproductive Toxicity: Contains no ingredient listed as toxic to reproduction.

Specific Target Organ Toxicity:

Single Exposure: Not classified

Repeated Exposure: Not classified

Aspiration Hazard: Not classified

Potential Chronic Health Effects: May be irritating to skin. Prolonged or repeated contact may

cause drying and cracking of the skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Component	Test	Species	Result
Alkanes, C21-28, chloro	LC50, 96 hours	Pimephales promelas	>100 mg/L
	LC50, 96 hours	Oncorhynchus mykiss	>300 mg/L

Persistence and Degradability: No data available

Bioaccumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion,

photochemical ozone creation potential, endocrine disruption, global

warming potential) are expected from this product.

13. DISPOSAL CONSIDERATIONS

Waste Disposal methods

Disposal of waste material should comply with all local, state, federal and provincial environmental regulations. See Section 7 for safe handling procedures and section 8 for personal protective equipment recommendations. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Empty containers or liners may retain some product residues. Follow label warnings even after container is emptied. Avoid contact of any spilled material or runoff with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT: Not dangerous/hazardous goods **IMDG:** Not dangerous/hazardous goods

15. REGULATORY INFORMATION

U.S. Federal Regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

United States Inventory

All components are listed or exempted.

(TSCA 8b)

SARA 302/304:

Composition/Information on Ingredients

No products were found

SARA Hazard Categories (311/312)

Acute Health Hazard: Yes
Chronic Health Hazard: No
Fire Hazard: No
Sudden Release of Pressure Hazard: No
Reactive Hazard: No

SARA 313

No products were found

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

No products were found.

16. OTHER INFORMATION

The information and recommendations contained within this document are believed by PetroChoice to be accurate and reliable as of the date prepared. The information and recommendations are offered for the user's consideration and analysis and in no way guarantee the chemical specifications for the specified product. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense arising out of the product's improper use. The user should consider the information in this document in the context of how the selected product will be handled and used in conjunction with other products. It is the user's responsibility to determine that the product is suitable for the intended use.

Appropriate warnings and safe-handling procedures should be provided to all handlers and users. PetroChoice assumes no responsibility for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices within this document.

Rev. Date: 7/3/2017